



Product Catalog



**Transfer Tanks and
Accessories**



Prices effective
March 2024
Prices Include GST

☰ Transfer Tanks and Accessories



Diesel Transfer Tank with Pump, 12V, 40LPM - 100L

\$795.00

Model: DD100

Volume: 100L

Power: 280W

Voltage: 12VDC

Current: 22A

Maximum Operating Time: 30min

RPM: 2600

Flow (LPM): 40

Outlet Hose Size: 19.05mm (3/4")

Priming: Self Priming

Hose Length: 4m

Power Cord Length: 4m

Size: 800(L) x 757(W) x 450(H)mm

Weight NW: 23Kg

Includes:

Battery Clamps

Features:

High quality trigger nozzle swivel with automatic cut off.

Safety internal pump bypass

Tank made from impact resistant polyethylene UV stabilized

Highly durable pad lockable cover

Internal suction foot filter

Heavy duty battery clamps with inline fuse

Suitable for Diesel only



Diesel Transfer Tank with Pump, 12V, 40LPM - 200L

\$895.00

Model: DD200

Volume: 200L

Power: 280W

Voltage: 12VDC

Current: 22A

Maximum Operating Time: 30min

RPM: 2600

Flow (LPM): 40

Outlet Hose Size: 19.05mm (3/4")

Priming: Self Priming

Hose Length: 4m

Power Cord Length: 4m

Size: 1150(L) x 770(W) x 550(H)mm

Weight NW: 35.8Kg

Includes:

Battery Clamps

Features:

High quality trigger nozzle swivel with automatic cut off.

Safety internal pump bypass

Tank made from impact resistant polyethylene UV stabilized

Highly durable pad lockable cover

Internal suction foot filter

Heavy duty battery clamps with inline fuse

Suitable for Diesel only.



Diesel Transfer Tank with Pump, 12V, 40LPM - 500L

\$1,435.00

Model: DD500
Volume: 500L
Power: 280W
Voltage: 12VDC
Current: 22A
Maximum Operating Time: 30min
RPM: 2600
Flow (LPM): 40
Outlet Hose Size: 19.05mm (3/4")
Priming: Self Priming
Hose Length: 4m
Power Cord Length: 4m
Size: 1720(L) x 760(W) x 760(H)mm
Weight NW: 57.6Kg

Includes:
Battery Clamps

Features:
High quality trigger nozzle swivel with automatic cut off.
Safety internal pump bypass
Tank made from impact resistant polyethylene UV stabilized
Highly durable pad lockable cover
Internal suction foot filter
Heavy duty battery clamps with inline fuse.

Suitable for Diesel only



Diesel Transfer Tank with Pump, 12V, 56LPM - 1000L

\$3,495.00

Model: DD980
Volume: 1000L
Power: 450W
Voltage: 12VDC
Current: 15A
Maximum Operating Time: 30min
RPM: 2800/3400
Flow (LPM): 56
Outlet Hose Size: 19.05mm (3/4")
Priming: Self Priming
Hose Length: 10m
Power Cord Length: 6m
Size: 1100(L) x 1300(W) x 1200(H)mm
Weight NW: 128Kg

Includes:
Battery Clamps

Features:
High quality trigger nozzle swivel with automatic cut off.
Safety internal pump bypass
Tank made from impact resistant polyethylene UV stabilized
Highly durable pad lockable cover
Internal suction foot filter
Heavy duty battery clamps with inline fuse.
Water Separator Filter
Led Lid Light
Diesel Level Gauge
Retractable Hose Reel

Suitable for Diesel only

≡ Transfer Tanks and Accessories



Adblue Transfer Tank with Pump, 12V, 26LPM - 400L

\$1,595.00

Model: AD400
Volume: 400L
Power: 240W
Voltage: 12VDC
Current: 10A
Maximum Operating Time: 30min
RPM: 2900
Flow (LPM): 26
Outlet Hose Size: 19.05mm (3/4")
Priming: Self Priming
Hose Length: 4m
Power Cord Length: 4m
Size: 1100(L) x 640(W) x 610(H)mm
Weight NW: 49Kg

Includes:
Battery Clamps

Features:
High quality trigger nozzle swivel with automatic cut off.
Tank made from impact resistant polyethylene UV stabilized
Highly durable pad lockable cover
Internal suction foot filter
Heavy duty battery clamps with inline fuse

Suitable for Diesel Exhaust Fluid (AdBlue) only



Diesel Transfer Pump - 12V, 40LPM

\$225.00

Model: DP40012K
Power: 180W
Voltage: 12VDC
Current: 15A
Maximum Operating Time: 30min
RPM: 4300
Flow (LPM): 40
Outlet Hose Size: 19.05mm (3/4")
Priming: Self Priming
Hose Length: 2m
Power Cord Length: 2m

Includes:
Battery Clamps
Internal suction foot filter
Mounting Bracket

Suitable for Diesel only



**Diesel Transfer Pump -
12V, 40LPM**

\$249.00

*Model: DP40012K-N
Power: 180W
Voltage: 12VDC
Current: 15A
Maximum Operating Time: 30min
RPM: 4300
Flow (LPM): 40
Outlet Hose Size: 19.05mm (3/4")
Priming: Self Priming
Hose Length: 2m
Power Cord Length: 2m*

*Includes:
Battery Clamps
Internal suction foot filter
Mounting Bracket*

Suitable for Diesel only



**Fuel Nozzle - 73PSI -
19.05mm (3/4")**

\$39.95

*Model: J60 Nozzle
Maximum Flow (LPM): 60
Maximum Pressure: 72.5PSI / 5Bar
Outlet Hose Size: 19.05mm (3/4")*

Features:

*Made of high quality aluminium
Trigger Lock*

≡ Transfer Tanks and Accessories



**Fuel Nozzle - Auto Shut Off,
Flow Sensor - 60PSI -
19.05mm(3/4")**

\$199.00

Model: NW01-A
Maximum Flow (LPM): 120
Maximum Pressure: 290PSI / 20Bar
Outlet Hose Size: 19.05mm (3/4")
Standby Battery Time: ~2 Years
Single Fuel Count: 0-9999L
Accumulated Fuel Count: 0-999999
Units: L / GAL / PTS / QTS
IP Rating: 54

Features:

Made of high quality aluminium
Measures flow rate, single use fuel count & total use fuel count.
Swivel Fitting
Trigger Lock
Auto Shut Off
Suitable for Diesel, Urea, Kerosene, Chemicals, Petrol



**Adblue Nozzle -Auto Shut
Off, Flow Sensor - 51PSI -
19.05mm (3/4")**

\$295.00

Model: AD13PP
Maximum Flow (LPM): 30
Maximum Pressure: 60PSI / 3 Bar
Outlet Hose Size: 19.05mm (3/4")
Standby Battery Time: ~2 Years
Single Fuel Count: 0-9999L
Accumulated Fuel Count: 0-999999
Units: L / GAL / PTS
IP Rating: 54

Includes: 2 Nozzle Low Flow (10Lpm) & High Flow 30(Lpm)

Features:

Measures flow rate, single use AdBlue count & total use Ad-Blue count.
Trigger Lock
Auto Shut Off
Suitable for Diesel Exhaust Fluid (AdBlue) only



CONTACT US

Phone:

(03) 313 1415

Email:

Sales@GoodsDirect2U.co.nz

Web:

www.GoodsDirect2U.co.nz

Address:

589 Mount Thomas Road, RD1,
Fernside, New Zealand 7471

Opening Hours:

9am - 5pm Monday-Friday

10am - 12noon Saturday