



Product Catalog



Prices effective
November 2023
Prices Include GST



**Winch - Electric 24V DC,
Steel Cable, Wired /
Wireless - 6804kg
(15000lbs)**

\$1,195.00

Model: RH15000-W-24V
 Rated Line Pull: 6804kg (15000lbs) Single Line
 Motor Type: Permanent Magnet
 Voltage: 24 Volts DC
 Input Power 7.35HP (5.4kw)
 Max. Motor Current: 223Amp
 Remote: Wired
 Gear Ratio: 315:1
 Gear Train: 3 Stage planetary
 Break: Automatic Load-holding Brake
 Power Out: Yes
 Power In: Yes
 Free Spooling: Yes
 Drum Diameter: 102mm
 Drum Width: 254mm
 Line Speed: 1.4m/min with Max. Line Pull
 Rope Material: Steel Cable
 Rope Diameter and Length: 12.7mm x 22m
 Hook: 11.1mm (7/16") with safety Catch
 Fairlead: Steel Cable
 Width Dimension: 662(L) x 214(H) x 245(D)mm
 Mounting Bolt Pattern: 304.8x 114.3mm
 IP Rating: IP67
 Weight NW: 64kg



**Winch - Electric 24V DC,
Steel Cable, Wired /
Wireless - 5445kg
(12000lbs)**

\$699.00

Model: RES12000-WLW-24V
 Rated Line Pull: 5445kg (12000lbs) Single Line
 Motor Type: Permanent Magnet
 Voltage: 24 Volts DC
 Input Power 4.9HP (3.6kw)
 Max. Motor Current: 220Amp
 Remote: Wired
 Gear Ratio: 294:1
 Gear Train: 3 Stage planetary
 Break: Automatic Load-holding Brake
 Power Out: Yes
 Power In: Yes
 Free Spooling: Yes
 Drum Diameter: 67mm
 Drum Width: 212mm
 Line Speed: 2.5m/min with Max. Line Pull
 Rope Material: Steel Cable
 Rope Diameter and Length: 9.5mm x 28m
 Hook: 9.5mm (3/8") with safety Catch
 Fairlead: Roller
 Width Dimension: 540(L) x 161(H) x 217(D)mm
 Mounting Bolt Pattern: 254 x 114.3mm
 IP Rating: IP67
 Weight NW: 37.2kg



**Winch - Electric 12V DC,
Synthetic Cable, Wired /
Wireless - 5445kg
(12000lbs)**

\$819.00

Model: RES12000SR-WLW-12V
 Rated Line Pull: 5445kg (12000lbs) Single Line
 Motor Type: Permanent Magnet
 Voltage: 12 Volts DC
 Input Power 4.9HP (3.6kw)
 Max. Motor Current: 320Amp
 Remote: Wired and Wireless
 Gear Ration: 294:1
 Gear Train: 3 Stage planetary
 Break: Automatic Load-holding Brake
 Power Out: Yes
 Power In: Yes
 Free Spooling: Yes
 Drum Diameter: 67mm
 Drum Width: 222mm
 Line Speed: 1.5m/min with Max. Line Pull
 Rope Material: Synthetic
 Rope Diameter and Length: 9.5mm x 28m
 Hook: 9.5mm (3/8") with safety Catch
 Fairlead: Aluminium Hawse
 Width Dimension: 540(L) x 161(H) x 217(D)mm
 Mounting Bolt Pattern: 254 x 114.3mm
 IP Rating: IP67
 Weight NW: 28.6kg



**Winch - Electric 12V DC,
Steel Cable, Wired /
Wireless - 5445kg
(12000lbs)**

\$629.00

Model: RES12000-WLW-12V
 Rated Line Pull: 5445kg (12000lbs) Single Line
 Motor Type: Permanent Magnet
 Voltage: 12 Volts DC
 Input Power 4.9HP (3.6kw)
 Max. Motor Current: 320Amp
 Remote: Wired and Wireless
 Gear Ration: 294:1
 Gear Train: 3 Stage planetary
 Break: Automatic Load-holding Brake
 Power Out: Yes
 Power In: Yes
 Free Spooling: Yes
 Drum Diameter: 67mm
 Drum Width: 222mm
 Line Speed: 1.5m/min with Max. Line Pull
 Rope Material: Steel Cable
 Rope Diameter and Length: 9.5mm x 28m
 Hook: 9.5mm (3/8") with safety Catch
 Fairlead: Roller
 Width Dimension: 540(L) x 161(H) x 217(D)mm
 Mounting Bolt Pattern: 254 x 114.3mm
 IP Rating: IP67
 Weight NW: 37.2kg



**Winch - Electric 12V DC,
Synthetic Cable, Wired /
Wireless - 4313kg
(9500lbs)**

\$789.00

*Model: RES9500SR-WLW-12V
Rated Line Pull: 4313kg (9500lbs) Single Line
Motor Type: Permanent Magnet
Voltage: 12 Volts DC
Input Power 4.9HP (3.6kw)
Max. Motor Current: 330Amp
Remote: Wired and Wireless
Gear Ratio: 210:1
Gear Train: 3 Stage planetary
Break: Automatic Load-holding Brake
Power Out: Yes
Power In: Yes
Free Spooling: Yes
Drum Diameter: 67mm
Drum Width: 212mm
Line Speed: 2.4m/min with Max. Line Pull
Rope Material: Synthetic
Rope Diameter and Length: 9.5mm x 28m
Fairlead: Aluminium Hawse
Width Dimension: 540(L) x 161(H) x 217(D)mm
Mounting Bolt Pattern: 254 x 114.3mm
IP Rating: IP67
Weight NW: 28.6kg*



**Winch - Electric 12V DC,
Steel Cable, Wired /
Wireless - 4313kg
(9500lbs)**

\$565.00

*Model: RES9500-WLW-12V
Rated Line Pull: 4313kg (9500lbs) Single Line
Motor Type: Permanent Magnet
Voltage: 12 Volts DC
Input Power 4.9HP (3.6kw)
Max. Motor Current: 330Amp
Remote: Wired and Wireless
Gear Ratio: 210:1
Gear Train: 3 Stage planetary
Break: Automatic Load-holding Brake
Power Out: Yes
Power In: Yes
Free Spooling: Yes
Drum Diameter: 67mm
Drum Width: 212mm
Line Speed: 2.4m/min with Max. Line Pull
Rope Material: Steel
Rope Diameter and Length: 9.5mm x 28m
Hook: 9.5mm (3/8") with safety Catch
Fairlead: Roller
Width Dimension: 540(L) x 161(H) x 217(D)mm
Mounting Bolt Pattern: 254 x 114.3mm
IP Rating: IP67
Weight NW: 37.2kg*



**Winch - Electric 12V DC,
Synthetic Cable, Wired /
Wireless - 2720kg
(6000lbs)**

\$729.00

Model: RES6000SR-WLW-12V
Rated Line Pull: 2720kg (6000lbs) Single Line
Motor Type: Permanent Magnet
Voltage: 12 Volts DC
Input Power 4.6HP (3.4kw)
Max. Motor Current: 220Amp
Remote: Wired and Wireless
Gear Ratio: 210:1
Gear Train: 3 Stage planetary
Break: Automatic Load-holding Brake
Power Out: Yes
Power In: Yes
Free Spooling: Yes
Drum Diameter: 63mm
Drum Width: 124mm
Line Speed: 2.7m/min with Max. Line Pull
Rope Material: Synthetic
Rope Diameter and Length: 7.14mm x 24m
Hook: 7.9mm (5/16") with safety Catch
Fairlead: Aluminium Hawse
Width Dimension: 452(L) x 161(H) x 217(D)mm
Mounting Bolt Pattern: 166 x 114.3mm
IP Rating: IP67
Weight NW: 25.5kg



**Winch - Electric 12V DC,
Steel Cable, Wired /
Wireless - 2720kg
(6000lbs)**

\$519.00

Model: RES6000-WLW-12V
Rated Line Pull: 2720kg (6000lbs) Single Line
Motor Type: Permanent Magnet
Voltage: 12 Volts DC
Input Power 4.6HP (3.4kw)
Max. Motor Current: 220Amp
Remote: Wired and Wireless
Gear Ratio: 210:1
Gear Train: 3 Stage planetary
Break: Automatic Load-holding Brake
Power Out: Yes
Power In: Yes
Free Spooling: Yes
Drum Diameter: 63mm
Drum Width: 124mm
Line Speed: 2.7m/min with Max. Line Pull
Rope Material: Steel Cable
Rope Diameter and Length: 7.14mm x 24m
Hook: 7.9mm (5/16") with safety Catch
Fairlead: Roller
Width Dimension: 452(L) x 161(H) x 217(D)mm
Mounting Bolt Pattern: 166 x 114.3mm
IP Rating: IP67
Weight NW: 29.5kg



**Winch - Electric 12V DC,
Steel Cable, Wired -
2270kg (5000lbs)**

\$315.00

Model: RP5000-W-12V
 Rated Line Pull: 2270kg (5000lbs) Single Line
 Motor Type: Permanent Magnet
 Voltage: 12 Volts DC
 Input Power 3.8HP (2.8kw)
 Max. Motor Current: 230Amp
 Remote: Wired
 Gear Ratio: 165:1
 Gear Train: 3 Stage planetary
 Break: Automatic Load-holding Brake
 Power Out: Yes
 Power In: Yes
 Free Spooling: Yes
 Drum Diameter: 50mm
 Drum Width: 137.5mm
 Line Speed: 2.8m/min with Max. Line Pull
 Rope Material: Steel Cable
 Rope Diameter and Length: 6.3mm x 15m
 Hook: 6.35mm (1/4") with safety Catch
 Fairlead: Roller
 Width Dimension: 397(L) x 117(H) x 120(D)mm
 Mounting Bolt Pattern: 76 x 168mm
 IP Rating: IP67
 Weight NW: 15.3kg



**Winch - Electric 12V DC,
Steel Cable, Wired -
1589kg (3500lbs)**

\$249.00

Model: RP3500-W-12V
 Rated Line Pull: 1589kg (3500lbs) Single Line
 Motor Type: Permanent Magnet
 Voltage: 12 Volts DC
 Input Power 3.1HP (2.3kw)
 Max. Motor Current: 200Amp
 Remote: Wired
 Gear Ratio: 136:1
 Gear Train: 3 Stage planetary
 Break: Automatic Load-holding Brake
 Power Out: Yes
 Power In: Yes
 Free Spooling: Yes
 Drum Diameter: 50mm
 Drum Width: 92.5mm
 Line Speed: 2.3m/min with Max. Line Pull
 Rope Material: Steel Cable
 Rope Diameter and Length: 5.56mm x 12.8m
 Hook: 6.35mm (1/4") with safety Catch
 Fairlead: Roller
 Width Dimension: 363(L) x 117(H) x 120(D)mm
 Mounting Bolt Pattern: 76.2 x 124mm
 IP Rating: IP67
 Weight NW: 11.3kg



**Winch - Electric 12V DC,
Stainless Cable, Wired -
908kg (2000lbs)**

\$325.00

*Model: REW2000SS-W-12V
Rated Line Pull: 908kg (2000lbs) Single Line
Motor Type: Permanent Magnet
Voltage: 12 Volts DC
Input Power 1.9HP (1.4kw)
Max. Motor Current: 115Amp
Remote: Wired
Gear Ratio: 153:1
Gear Train: 2 Stage planetary
Break: Automatic Load-holding Brake
Power Out: Yes
Power In: Yes
Free Spooling: Yes
Drum Diameter: 32mm
Drum Width: 72m
Drum Material: Stainless Steel
Line Speed: 1.8m/min with Max. Line Pull
Rope Material: Stainless Steel
Rope Diameter and Length: 4mm x 15m
Hook: 4.8mm (3/16") with safety Catch
Fairlead: Roller
Width Dimension: 320(L) x 105(H) x 110.5(D)mm
Mounting Bolt Pattern: 254.4 x 76mm
IP Rating: IP67
Weight NW: 6.6kg*



**Winch - Electric 12V DC,
Steel Cable, Wireless -
908kg (2000lbs)**

\$139.00

*Model: RP2000-WL-12V
Rated Line Pull: 908kg (2000lbs) Single Line
Motor Type: Permanent Magnet
Voltage: 12 Volts DC
Input Power 1.9HP (1.4kw)
Max. Motor Current: 115Amp
Remote: Wireless
Gear Ratio: 153:1
Gear Train: 2 Stage planetary
Break: Automatic Load-holding Brake
Power Out: Yes
Power In: Yes
Free Spooling: Yes
Drum Diameter: 32mm
Drum Width: 72m
Drum Material: Aluminium
Line Speed: 1.8m/min with Max. Line Pull
Rope Material: Steel Cable
Rope Diameter and Length: 4mm x 15m
Hook: 4.8mm (3/16") with safety Catch
Fairlead: Roller
Width Dimension: 285.5(L) x 113(H) x 107.5(D)mm
Mounting Bolt Pattern: 254.4 x 76mm
IP Rating: IP67
Weight NW: 6.5kg*



**Winch - Hydraulic, Steel
Cable - 8165kg (18000lbs)**

\$1,950.00

Model: RYW18
Rated Line Pull: 8,165kg (18,000lbs) Single Line
Motor Type: Hydraulic
Displacement: 124.9cm³/Rev
Operation Pressure: 2030PSI (140 Bar)
Max Oil Flow: 75L/Min (20 GPM)
Rotation: Anti-Clockwise
Gear Ratio: 36:01:00
Gear Train: 2 Stage Planetary
Break: Heavy Duty Automatic Disk
Power Out: Yes
Power In: Yes
Free Spooling: Yes
Drum Diameter: 102mm
Drum Width: 253mm
Line Speed: 4m/min with Max. Line Pull
Rope Material: Steel Cable
Rope Diameter and Length: 12.7mm x 22m
Hook: 11.1mm (7/16") with safety Catch
Fairlead: Roller
Sound Rating: 85db
Dimension: 662(L) x 244(H) x 214(D)mm
Mounting Bolt Pattern: 114.3 x 304.8mm & 165 x 304.8mm
Weight NW: 68kg



**Winch - Hydraulic, Steel
Cable - 4082kg (9000lbs)**

\$1,745.00

Model: RYW09
Rated Line Pull: 4,082kg (9,000lbs) Single Line
Motor Type: Hydraulic
Displacement: 80.6cm³/Rev
Operation Pressure: 2030PSI (140 Bar)
Max Oil Flow: 75L/Min (20 GPM)
Rotation: Clockwise
Gear Ratio: 21.7:1
Gear Train: 2 Stage Planetary
Break: Heavy Duty Automatic Disk
Power Out: Yes
Power In: Yes
Free Spooling: Yes
Drum Diameter: 102mm
Drum Width: 253mm
Line Speed: 10.4m/min with Max. Line Pull
Rope Material: Steel Cable
Rope Diameter and Length: 9.53mm x 30.5m
Hook: 9.5mm (3/8") with safety Catch
Fairlead: Roller
Sound Rating: 85db
Dimension: 662(L) x 244(H) x 214(D)mm
Mounting Bolt Pattern: 114.3 x 304.8mm & 165 x 304.8mm
Weight NW: 62kg

RP / RES - Winch Remote

\$22.00

Model: FEWLO7

RP / RES - Winch Remote -
Premium

\$55.00

Model: FECD01



CONTACT US

Phone:

(03) 313 1415

Email:

Sales@GoodsDirect2U.co.nz

Web:

www.GoodsDirect2U.co.nz

Address:

589 Mount Thomas Road, RD1,
Fernside, New Zealand 7471

Opening Hours:

9am - 5pm Monday-Friday

10am - 12noon Saturday