



Product Catalog



*Electric, 2 and 4 Stroke
Outboard Motors*



Prices effective
May 2023
Prices Include GST

KNK
The Power Pro®



**Outboard Motor -
Petrol, 2 Stroke - 2HP**

\$329.00

Model: KM0405520-S
Motor: KM1E44F-2
Displacement: 51.7cc
Power: 1.4kW, 2HP
Start: Pull
Fuel Type: 2 Stroke, 25:1
Propeller: Metal
Transom Height: 405-430mm
Weight NW: 9.5kg

KNK
The Power Pro®



**Outboard Motor -
Petrol, 4 Stroke - 1.2HP**

\$419.00

Model: KM0405331
Motor: KM139F-2
Displacement: 33.5cc
Power: 1.2HP
Start: Pull
Fuel Type: 4 Stroke
Propeller: Metal
Transom Height:
Weight NW: 10.57kg

NERAUS®

ELECTRIC OUTBOARD MOTORS



Neraus X-Series Trolling Motor:

- Modern design*
- Adjustable telescopic throttle handle*
- Anti-corrosive & Anti-rust coating materials*
- LED battery meter*
- Durable Aluminium Alloy*
- Adjustable control box angle*
- Transom height adjustable*
- Motor can be tilted when out of water*



Neraus L-Series Trolling Motor:

- Modern design*
- Fixed throttle handle*
- Anti-corrosive coating suitable for salt water*
- LED battery meter*
- Durable Aluminium Alloy*
- Fixed control box angle*
- Transom height adjustable*
- Motor can be tilted when out of water*



Outboard Motor - DC - Long Shaft - 46lb

\$329.00

Model: NRS-46X-36
Head: Durable Aluminium
Trust: 20.9kg (46lb)
Control Module: Turned up or Down +/- 30 Degrees
Handle: 15cm Telescopic
Battery Indicator: 10 Point
Input Voltage: 12V
Input Current: 40A
Input Power: 480W
Speeds: 5 Forward, 3 Reverse
Shaft: Composite Fibre Glass 914mm (36")
Mount: Strong Nylon
Propeller: 3 Blade Machete
Max. Boat Weight: 940kg
Weight NW: 8.1kg



Outboard Motor - DC - Long Shaft - 55lb

\$359.00

Model: NRS-55X-36
Head: Durable Aluminium
Trust: 25.0kg (55lb)
Control Module: Turned up or Down +/- 30 Degrees
Handle: 15cm Telescopic
Battery Indicator: 10 Point
Input Voltage: 12V
Input Current: 52A
Input Power: 624W
Speeds: 5 Forward, 3 Reverse
Shaft: Composite Fibre Glass 914mm (36")
Mount: Strong Nylon
Propeller: 3 Blade Machete
Max. Boat Weight: 1150kg
Weight NW: 9.6kg



**Outboard Motor - DC -
Short Shaft - 62lb**

\$419.00

*Model: NRS-62X-24
Head: Durable Aluminium
Trust: 28.2kg (62lb)
Control Module: Turned up or Down +/- 30 Degrees
Handle: 15cm Telescopic
Battery Indicator: 10 Point
Input Voltage: 12V
Input Current: 58A
Input Power: 696W
Speeds: 5 Forward, 3 Reverse
Shaft: Composite Fibre Glass 609mm (24")
Mount: Strong Nylon
Propeller: 3 Blade Machete
Max. Boat Weight: 1290kg
Weight NW: 9.6kg*



**Outboard Motor - DC -
Long Shaft - 62lb**

\$425.00

*Model: NRS-62X-36
Head: Durable Aluminium
Trust: 28.2kg (62lb)
Control Module: Turned up or Down +/- 30 Degrees
Handle: 15cm Telescopic
Battery Indicator: 10 Point
Input Voltage: 12V
Input Current: 58A
Input Power: 696W
Speeds: 5 Forward, 3 Reverse
Shaft: Composite Fibre Glass 914mm (36")
Mount: Strong Nylon
Propeller: 2 Blade Machete
Max. Boat Weight: 1290kg
Weight NW: 9.7kg*



Outboard Motor - DC - Long Shaft—86lb

\$445.00

Model: NRS-86X-36
Head: Durable Aluminium
Trust: 37.2kg (86lb)
Control Module: Turned up or Down +/- 30 Degrees
Handle: 15cm Telescopic
Battery Indicator: 10 Point
Input Voltage: 24V
Input Current: 48A
Input Power: 1152W
Speeds: 5 Forward, 3 Reverse
Shaft: Composite Fibre Glass 1016mm (40")
Mount: Strong Nylon
Propeller: 2 Blade Machete
Max. Boat Weight: 1650kg
Weight NW: 10.2kg



Outboard Motor - DC, Salt Water - Short Shaft - 62lb

\$419.00

Model: NRS-62L-24S
Head: Durable Aluminium
Trust: 28.2kg (62lb)
Handle: 15cm Telescopic
Battery Indicator: 10 Point
Input Voltage: 12V
Input Current: 58A
Input Power: 696W
Speeds: 5 Forward, 3 Reverse
Shaft: Composite Fibre Glass 609mm (24")
Mount: Strong Nylon
Propeller: 3 Blade Machete
Max. Boat Weight: 1290kg
Weight NW: 11kg



Outboard Motor - DC, Salt Water - Long Shaft - 62lb

\$425.00

*Model: NRS-62L-36S
Head: Durable Aluminium
Trust: 28.2kg (62lb)
Handle: 15cm Telescopic
Battery Indicator: 10 Point
Input Voltage: 12V
Input Current: 58A
Input Power: 696W
Speeds: 5 Forward, 3 Reverse
Shaft: Composite Fibre Glass 914mm (36")
Mount: Strong Nylon
Propeller: 3 Blade Machete
Max. Boat Weight: 1290kg
Weight NW: 11.4kg*



Smart Battery Box - 60A

\$99.00

*Model: Smart Battery Box
Ports: USB and 12VDC
Circuit Breakers: 60Amp and 10Amp
Meter: Blue-LED
Colour: Black
Internal Size: 335(L) x 180(W) x 220(H)mm*

Great way of battery power management, various functions to support DC accessories

Designed to provide a simple and convenient way to manage power. The smart battery box is a great companion for small boats and trolling motors. The case is strong and waterproof, which is very capable for heavy duty usage. The smart battery box also provides multiple function: USB charger, 12V DC port and blue-LED battery meter. In addition, two embedded circuit breakers help to prevent any accident faults or improper connections

≡ Outboard Motors



Outboard Motor - DC - 46lb - Leg

\$159.95

Model: NRS-46X - Leg
Trust: 46lb
Voltage: 12V
Shaft: Composite Fibre Glass
Propeller: 3 Blade Machete



Outboard Motor - DC - 55lb - Leg

\$190.00

Model: NRS-55X - Leg
Trust: 55lb
Voltage: 12V
Shaft: Composite Fibre Glass
Propeller: 3 Blade Machete

Model	Thrust in lbs	Thrust in kg	Input	Input Power	Max Speed
NRS-46L	46	20.9	12V, 40A	480W	9.5kph *
NRS-55L	55	25.0	12V, 52A	624W	14.5kph *
NRS-62L	62	28.2	12V, 58A	696W	18kph *
NRS-86L	86	37.2	24V, 48A	1152W	16kph *

NOTE: * Since Speed depends on many factors such as loading, water conditions, hull type and wind speed etc., it would be difficult to give accurate speed rating, we give the speed for reference purposes:
Boat size 2.3m, loading 90kg, quiet water

BATTERY TYPE: Recommended Battery(s): 12 Volt Deep Cycle battery or Marine battery, battery should have at least 50 ampere hour rating or higher. To extend the running time either a larger battery or an additional battery can be used. (Note NRS-86L requires a 24 Volt Battery)



**Outboard Motor - DC -
62lb - Leg**

\$219.00

Model: NRS-62X-LEG

Trust: 62lb

Voltage: 12V

Shaft: Composite Fibre Glass

Propeller: 3 Blade Machete



Kayak Outboard Motor - Digital Control, Brushless Motor - DC - 60lb

\$1,595.00

Model: NK-180S
Trust: 27.2kg (60lb) 1.8HP
Battery Type: Lithium or Lead-Acid
Battery Cable Length: 177mm
Input Voltage: 24V
Input Current: 25A
Input Power: 600W
Max Propeller Speed: 1800rpm
Shaft Length: 500mm (19.7")
Shaft Dia.: 29.21mm
Mounting Bracket Overall Size: 356(L) x 153(W)mm
Min. Mount Size: 140(L) x 115(W)mm
Propeller: 2 Blade
Weight NW: 6.5kg

Features:

24V Brushless Motor: The 1.8hp equivalent Direct Drive motor provides quiet and efficient power delivery without the use of internal gears, powering you along at up to 5 knots!

Designed for fishing kayaks

Four bolt aluminium mount.

Features trim adjustment

Integrated rudder steering

Stow/deploy motor with pull of a cord

Three Steering Cable Setup Options

- No Steering - Motor used for forward and reverse only
- Cable routing goes through stern of kayak
- Cable routing goes above the deck of the kayak



Outboard Motor - 2 Stroke - Short Shaft - 2.2HP

\$595.00

Model: PNT2.2 Short Shaft
 Motor Type: 1 Cylinder, 1 Carb.
 Displacement: 50cc
 Bore x Stroke: 42 x 36mm
 Gear Ratio: 2.08
 Full Throttle Speed Range: 4000-5000
 Idling: 1050 +/- 50RPM
 Starter: Manual
 Internal Fuel Tank: 1.2L
 External Fuel Connection: No
 Direction System: Manual
 Max. Prop Shaft Output: 1.6kW @ 5000rpm
 Engine Transom Height: 381mm (Short Shaft)
 Trim and Tilt: Manual
 Dry Weight: 10kg



Outboard Motor - 2 Stroke - Short Shaft - 5.0HP

\$1,325.00

Model: PNT5 Short Shaft
 Motor Type: 1 Cylinder, 1 Carb.
 Displacement: 103cc
 Bore x Stroke: 54 x 45mm
 Gear Ratio: 2.08
 Full Throttle Speed Range: 4500-5500
 Idling: 1150 +/- 50RPM
 Starter: Manual
 Internal Fuel Tank: 2.8L
 External Fuel Connection: Yes
 Direction System: Manual
 Max. Prop Shaft Output: 3.7kW (5HP) @ 5000rpm
 Alternator Output: N/A
 Engine Transom Height: 444mm (Short Shaft)
 Trim and Tilt: Manual
 Dry Weight: 20kg
 Included: 2M Fuel Hose with Primer and 12L Fuel Tank



**Outboard Motor - 2 Stroke
- Long Shaft - 5.0HP**

\$1,375.00

*Model: PNT5 Long Shaft
Motor Type: 1 Cylinder, 1 Carb.
Displacement: 103cc
Bore x Stroke: 54 x 45mm
Gear Ratio: 2.08
Full Throttle Speed Range: 4500-5500
Idling: 1150 +/- 50RPM
Starter: Manual
Internal Fuel Tank: 2.8L
External Fuel Connection: Yes
Direction System: Manual
Max. Prop Shaft Output: 3.7kW (5HP) @ 5000rpm
Alternator Output: N/A
Engine Transom Height: 571mm (Long Shaft)
Trim and Tilt: Manual
Dry Weight: 21.5kg
Included: 2M Fuel Hose with Primer and 12L Fuel Tank*



**Outboard Motor - 2 Stroke
- Short Shaft - 9.9HP**

\$2,239.00

*Model: PNT9.9 Short Shaft
Motor Type: 2 Cylinder, 1 Carb.
Displacement: 246cc
Bore x Stroke: 56 x 50mm
Gear Ratio: 2.08
Full Throttle Speed Range: 4500-5500
Idling: 750 +/- 50RPM
Starter: Manual
Direction System: Manual
Max. Prop Shaft Output: 7.4kW (9.9HP) @ 5000rpm
Alternator Output: 12V, 6A
Engine Transom Height: 440mm (Short Shaft)
Direction System: Manual
Dry Weight: 36kg
Included: 2M Fuel Hose with Primer and 24L Fuel Tank*



Outboard Motor - 2 Stroke - Long Shaft - 9.9HP

\$2,495.00

Model: PNT9.9 Long Shaft

Motor Type: 2 Cylinder, 1 Carb.

Displacement: 246cc

Bore x Stroke: 56 x 50mm

Gear Ratio: 2.08

Full Throttle Speed Range: 4500-5500

Idling: 750 +/- 50RPM

Starter: Manual

Direction System: Manual

Max. Prop Shaft Output: 7.4kW (9.9HP) @ 5000rpm

Alternator Output: N/A

Engine Transom Height: 567mm (Long Shaft)

Trim and Tilt: Manual

Dry Weight: 37.5kg

Included: 2M Fuel Hose with Primer and 24L Fuel Tank



Outboard Motor - 2 Stroke - Short Shaft - 15HP

\$2,425.00

Model: PNT15 Short Shaft

Motor Type: 2 Cylinder, 1 Carb.

Displacement: 246cc

Bore x Stroke: 56 x 50mm

Gear Ratio: 2.08

Full Throttle Speed Range: 4500-5500

Idling: 750 +/- 50RPM

Starter: Manual

Direction System: Manual

Max. Prop Shaft Output: 11.2kW (15HP) @ 5000rpm

Alternator Output: 12V, 6A with Rectifier / Regulator

Engine Transom Height: 440mm (Short Shaft)

Trim and Tilt: Manual

Dry Weight: 36kg

Included: 2M Fuel Hose with Primer and 24L Fuel Tank



**Outboard Motor - 2 Stroke
- Long Shaft - 15HP**

\$2,495.00

*Model: PNT15 Long Shaft
Motor Type: 2 Cylinder, 1 Carb.
Displacement: 246cc
Bore x Stroke: 56 x 50mm
Gear Ratio: 2.08
Full Throttle Speed Range: 4500-5500
Idling: 750 +/- 50RPM
Starter: Manual
Direction System: Manual
Max. Prop Shaft Output: 11.2kW (15HP) @ 5000rpm
Alternator Output: 12V, 6A with Rectifier / Regulator
Engine Transom Height: 567mm (Long Shaft)
Trim and Tilt: Manual
Dry Weight: 37.5kg
Included: 3M Fuel Hose with Primer and 24L Fuel Tank*



**Outboard Motor - 2 Stroke
- Short Shaft - 25HP**

\$2,995.00

*Model: PNT25 Short Shaft
Motor Type: 2 Cylinder, 1 Carb.
Displacement: 496cc
Bore x Stroke: 72 x 61mm
Gear Ratio: 2.08
Full Throttle Speed Range: 4500-5500
Idling: 1100 +/- 50RPM
Starter: Manual
Direction System: Manual
Max. Prop Shaft Output: 18.4kW (25HP) @ 5000rpm
Alternator Output: 12V, 6A with Rectifier / Regulator
Engine Transom Height: 381mm (Short Shaft)
Trim and Tilt: Manual
Dry Weight: 52kg
Included: 2M Fuel Hose with Primer and 24L Fuel Tank*



**Outboard Motor - 2 Stroke
- Long Shaft - 25HP**

\$3,035.00

*Model: PNT25 Long Shaft
Motor Type: 2 Cylinder, 1 Carb.
Displacement: 496cc
Bore x Stroke: 72 x 61mm
Gear Ratio: 2.08
Full Throttle Speed Range: 4500-5500
Idling: 1100 +/- 50RPM
Starter: Electric (Not Included) / Manual
Direction System: Remote (Not Included) / Manual
Max. Prop Shaft Output: 18.4kW (25HP) @ 5000rpm
Alternator Output: 12V, 6A with Rectifier / Regulator
Engine Transom Height: 508mm (Long Shaft)
Trim and Tilt: Manual
Dry Weight: 54.5kg
Included: 2M Fuel Hose with Primer and 24L Fuel Tank*



**Outboard Motor - 2 Stroke
- Long Shaft - 40HP**

\$4,449.00

*Model: PNT40E Long Shaft
Motor Type: 2 Cylinder, 1 Carb.
Displacement: 703cc
Bore x Stroke: 80 x 70mm
Gear Ratio: 2.0
Full Throttle Speed Range: 4500-5500
Idling: 1000 +/- 50RPM
Starter: Electric (Not Included) / Manual
Direction System: Remote (Not Included) / Manual
Max. Prop Shaft Output: 29.4kW (40HP) @ 5000rpm
Alternator Output: 12V, 6A with Rectifier / Regulator
Engine Transom Height: 550mm (Long Shaft)
Trim and Tilt: Manual and Power Trim
Dry Weight: 78kg
Included: 2M Fuel Hose with Primer and 24L Fuel Tank*



**Outboard Motor - 4 Stroke
- Short Shaft - 2.5HP**

\$995.00

*Model: PNF2.5 Short Shaft
Motor Type: 1 Cylinder, 1 Carb., OHV
Displacement: 72cc
Bore x Stroke: 54 x 31.5mm
Reduction Ratio: 9.0
Full Throttle Speed Range: 1.8kW (2.5HP) @ 5500rpm
Max rpm range: 5,250-5,750rpm
Ignition System: TCI
Engine Oil Capacity: 350mL
Fuel Tank Capacity: 900mL
Starter: Manual
Exhaust: Above Propeller
Cooling: Water / Thermostatic Control
Gear Ratio: 2.08
Gear Shift: Forward, Neutral
Engine Transom Height: 381mm (Short Shaft)
Trim and Tilt: Manual
Dry Weight: 17kg*

**Outboard Motor - 4 Stroke
- Short Shaft - 4HP**

\$1,379.00

*Model: PNF4 Short Shaft
Motor Type: 1 Cylinder, 1 Carb., OHV
Displacement: 139cc
Bore x Stroke: 62 x 46mm
Reduction Ratio: 8.90
Full Throttle Speed Range: 2.9kW (4HP) @ 5000rpm
Max rpm range: 4000-5000rpm
Ignition System: CDI
Engine Oil Capacity: 600mL
Starter: Manual
External Fuel Connection: Yes
Exhaust: Through Propeller
Cooling: Water / Thermostatic Control
Gear Ratio: 2.08
Gear Shift: Forward, Neutral, Reverse
Engine Transom Height: 435mm (Short Shaft)
Trim and Tilt: Manual
Dry Weight: 27kg*



Outboard Motor - 4 Stroke - Long Shaft - 4HP

\$1,439.00

Model: PNF4 Long Shaft
Motor Type: 1 Cylinder, 1 Carb., OHV
Displacement: 139cc
Bore x Stroke: 62 x 46mm
Reduction Ratio: 8.90
Full Throttle Speed Range: 2.9kW (4HP) @ 5000rpm
Max rpm range: 4000-5000rpm
Ignition System: CDI
Engine Oil Capacity: 600mL
Starter: Manual
External Fuel Connection: Yes
Exhaust: Above Propeller
Cooling: Water / Thermostatic Control
Gear Ratio: 2.08
Gear Shift: Forward, Neutral, Reverse
Engine Transom Height: 562mm (Long Shaft)
Trim and Tilt: Manual
Dry Weight: 28kg



Outboard Motor - 4 Stroke - Short Shaft - 6HP

\$1,439.00

Model: PNF6 Short Shaft
Motor Type: 1 Cylinder, 1 Carb., OHV
Displacement: 139cc
Bore x Stroke: 62 x 46mm
Reduction Ratio: 8.90
Full Throttle Speed Range: 4.4kW (6HP) @ 5500rpm
Max rpm range: 4000-5500rpm
Ignition System: CDI
Engine Oil Capacity: 600mL
Starter: Manual
Exhaust: Above Propeller
Cooling: Water / Thermostatic Control
Gear Ratio: 2.08
Gear Shift: Forward, Neutral, Reverse
Engine Transom Height: 435mm (Short Shaft)
Trim and Tilt: Manual
Dry Weight: 27kg
Included: 2M Fuel Hose with Primer and 12L Fuel Tank



**Outboard Motor - 4 Stroke
- Long Shaft - 6HP**

\$1,469.00

Model: PNF6 Long Shaft
Motor Type: 1 Cylinder, 1 Carb., OHV
Displacement: 139cc
Bore x Stroke: 62 x 46mm
Reduction Ratio: 8.90
Full Throttle Speed Range: 4.4kW (6HP) @ 5500rpm
Max rpm range: 4000-5500rpm
Ignition System: CDI
Engine Oil Capacity: 600mL
Starter: Manual
Exhaust: Above Propeller
Cooling: Water / Thermostatic Control
Gear Ratio: 2.08
Gear Shift: Forward, Neutral, Reverse
Engine Transom Height: 562mm (Long Shaft)
Trim and Tilt: Manual
Dry Weight: 28kg
Included: 2M Fuel Hose with Primer and 12L Fuel Tank



**Outboard Motor - 4 Stroke
- Short Shaft - 9.9HP**

\$2,735.00

Model: PNF9.9 Short Shaft
Motor Type: 2 Cylinder, 1 Carb., SOHV
Displacement: 212cc
Bore x Stroke: 56 x 43mm
Reduction Ratio: 9.40
Full Throttle Speed Range: 7.3kW (9.9HP) @ 5500rpm
Max rpm range: 5000-6000rpm
Ignition System: CDI
Alternator Output: 12V, 6A
Engine Oil Capacity: 1.8L
Starter: Manual
Exhaust: Through Propeller
Cooling: Water / Thermostatic Control
Gear Ratio: 2.08
Gear Shift: Forward, Neutral, Reverse
Engine Transom Height: 430mm (Short Shaft)
Trim and Tilt: Manual
Dry Weight: 37.5kg
Included: 2M Fuel Hose with Primer and 24L Fuel Tank



**Outboard Motor - 4 Stroke
- Long Shaft - 9.9HP**

\$2,785.00

Model: PNF9.9 Long Shaft
 Motor Type: 2 Cylinder, 1 Carb., SOHV
 Displacement: 212cc
 Bore x Stroke: 56 x 43mm
 Reduction Ratio: 9.40
 Full Throttle Speed Range: 7.3kW (9.9HP) @ 5500rpm
 Max rpm range: 5000-6000rpm
 Ignition System: CDI
 Alternator Output: 12V, 6A
 Engine Oil Capacity: 1.8L
 Starter: Manual
 Exhaust: Through Propeller
 Cooling: Water / Thermostatic Control
 Gear Ratio: 2.08
 Gear Shift: Forward, Neutral, Reverse
 Engine Transom Height: 557mm (Long Shaft)
 Trim and Tilt: Manual
 Dry Weight: 41.5kg
 Included: 2M Fuel Hose with Primer and 24L Fuel Tank



**Outboard Motor - 4 Stroke
- Short Shaft - 15HP**

\$2,850.00

Model: PNF15 Short Shaft
 Motor Type: 2 Cylinder, 1 Carb., SOHV
 Displacement: 362cc
 Bore x Stroke: 63 x 58.1mm
 Reduction Ratio: 9.30
 Full Throttle Speed Range: 11kW (15HP) @ 5500rpm
 Max rpm range: 5000-6000rpm
 Ignition System: CDI Micro Computer
 Alternator Output: 12V, 10A
 Engine Oil Capacity: 1.8L
 Starter: Manual / Electric
 Exhaust: Through Propeller
 Cooling: Water / Thermostatic Control
 Gear Ratio: 2.08
 Gear Shift: Forward, Neutral, Reverse
 Engine Transom Height: XXXmm (Short Shaft)
 Trim and Tilt: Manual
 Dry Weight: XX.Xkg
 Included: 2M Fuel Hose with Primer and 24L Fuel Tank



**Outboard Motor - 4 Stroke
- Long Shaft - 15HP**

\$2,879.00

*Model: PNF15 Long Shaft
Motor Type: 2 Cylinder, 1 Carb., SOHV
Displacement: 362cc
Bore x Stroke: 63 x 58.1mm
Reduction Ratio: 9.30
Full Throttle Speed Range: 11kW (15HP) @ 5500rpm
Max rpm range: 5000-6000rpm
Ignition System: CDI Micro Computer
Alternator Output: 12V, 10A
Engine Oil Capacity: 1.8L
Starter: Manual / Electric
Exhaust: Through Propeller
Cooling: Water / Thermostatic Control
Gear Ratio: 2.08
Gear Shift: Forward, Neutral, Reverse
Engine Transom Height: 570mm (Long Shaft)
Trim and Tilt: Manual
Dry Weight: 53.7kg
Included: 2M Fuel Hose with Primer*



**Outboard Motor - 4 Stroke
- Short Shaft - 20HP**

\$3,025.00

*Model: PNF20 Short Shaft
Motor Type: 2 Cylinder, 1 Carb., SOHV
Displacement: 362cc
Bore x Stroke: 63 x 58mm
Reduction Ratio: 27:13
Full Throttle Speed Range: 14.7kW (20HP) @ 5500rpm
Max rpm range: 5000-6000rpm
Ignition System: Microcomputer
Alternator Output: 12V, 5.5A @ 3000rpm to 15A @ 5000rpm
Engine Oil Capacity: 1.8L
Starter: Manual
Exhaust: Through Propeller
Cooling: Water / Thermostatic Control
Gear Ratio: 2.08
Gear Shift: Forward, Neutral, Reverse
Engine Transom Height (Whole Height): 1078mm (Short Shaft)
Trim and Tilt: Manual
Dry Weight: 51.7kg
Included: 2M Fuel Hose with Primer and 24L Fuel Tank*



Outboard Motor - 4 Stroke - Long Shaft - 20HP

\$3,075.00

Model: PNF20 Long Shaft

Motor Type: 2 Cylinder, 1 Carb., SOHV

Displacement: 362cc

Bore x Stroke: 63 x 58mm

Reduction Ratio: 27:13

Full Throttle Speed Range: 14.7kW (20HP) @ 5500rpm

Max rpm range: 5000-6000rpm

Ignition System: Microcomputer

Alternator Output: 12V, 5.5A @ 3000rpm to 15A @ 5000rpm

Engine Oil Capacity: 1.8L

Starter: Manual

Exhaust: Through Propeller

Cooling: Water / Thermostatic Control

Gear Ratio: 2.08

Gear Shift: Forward, Neutral, Reverse

Engine Transom Height (Whole Height): 1205mm (Long Shaft)

Trim and Tilt: Manual

Dry Weight: 53.7kg

Included: 2M Fuel Hose with Primer and 24L Fuel Tank



Outboard Fuel Hose - 2m

Model: Outboard Fuel Hose - 2m
 Hose Length: 2m
 Fitting Type: Two Prong
 Weight NW: 0.4kg
 Included: Primer and Connection Fittings
 Fits 12L and 24L fuel tank

\$39.95



Outboard - Propeller - PNT9.9, PNT15

Model: PNT9.9 / PNT15 PROPELLER
 Blades: 3
 Diameter: 235mm (9 1/4")
 Thread Pitch: 279mm (11")
 Spline: 8 Type: J
 Size: 3 x 9-1/4" x 11"-J
 Recommended HP:
 2 stroke 9.9-15 HP
 4 stroke 9.9-20 HP

\$92.00



Outboard Fuel Tank - 12L

Model: Outboard Fuel Tank - 12L
 Tank Capacity: 12L
 Fitting Type: Two Prong
 Size: 350(L) x 250(W) x 255(H)mm
 Weight NW: 1.5kg
 Included: Connection Fittings and Fuel Level Indicator
 Excludes fuel hose

\$54.00



Outboard - Propeller - PNT25, PNT30

Model: PNT25 / PNT30 PROPELLER
 Blades: 3
 Diameter: 200mm (7 7/8")
 Thread Pitch: 305mm (12")
 Spline: 10 Type: F
 Size: 3 x 9-7/8" x 12"-F
 Recommended HP:
 2 stroke 20-30 HP
 4 stroke 5-25 HP

\$95.00



Outboard Fuel Tank - 24L

Model: Outboard Fuel Tank - 24L
 Tank Capacity: 24L
 Fitting Type: Two Prong
 Size: 440(L) x 310(W) x 250(H)mm
 Weight NW: 2.65kg
 Included: Connection Fittings and Fuel Level Indicator
 Excludes fuel hose

\$85.00



Outboard - Propeller - PNT40, PNT60HPE

Model: PNT40 / PNF60HPE PROPELLER
 Blades: 3
 Diameter: 283mm (11 1/8")
 Thread Pitch: 330mm (13")
 Spline: 13 Type: G
 Size: 3 x 11-1/8" x 13"-G
 Recommended HP:
 2 stroke 40-50 HP
 4 stroke 30-60 HP

\$95.00

Outboard - Propeller - PNT2.5

Model: PNT2.5 PROPELLER
 Blades: 3
 Diameter: 185mm (7 1/4")
 Thread Pitch: 127mm (5")
 Spline Type: N/A (pin)
 NOTE Colour: White
 Size: 3 x 7-1/4" x 5"-A

\$34.95



Outboard - Propeller - PNT4, PNF5, PNT6, PNT5

Model: PNF4 / PNF5 / PNF6 / PNT5 PROPELLER
 Blades: 3
 Diameter: 190mm (7 1/2")
 Thread Pitch: 203mm (8")
 Spline: 9 Type: BA
 Size: 3 x 7-1/2" x 8"-BA

\$37.95



**Outboard - Propeller -
PNF9.9**

*Model: PNF9.9 PROPELLER
Blades: 3
Diameter: 215mm (8 1/2")
Thread Pitch: 210mm (8 1/2")
Spline: 7 Type: N
Size: 3 x 8-1/2" x 8-1/2"-N*

\$79.95



**Outboard - Propeller -
PNF15, PNF20**

*Model: PNF15 / PNF20
PROPELLER
Blades: 3
Diameter: 295mm (11 5/8")
Thread Pitch: 279mm (11")
Spline Type: G
Size: 3 x 11-5/8" x 11"-G*

\$69.95



CONTACT US

Phone: 03 313 1415

Fax: 03 313 1495

Email: sales@GoodsDirect2U.co.nz

Web: www.GoodsDirect2U.co.nz

Address: 589 Mount Thomas Road,
RD1,
Fernside
New Zealand

Opening Hours: 9am - 5:00pm Mon-Fri
10am - 12am Sat.
